




# AIRSOFT PERFORMANCE



- 1 Extra-soft smooth black non-staining and oil resistant PVC
- 2, 4 Intermediate layer in extra-soft black PVC
- 3 Polyester reinforcement
- 5 Extra-soft red oil resistant PVC

## APPLICATIONS

Pneumatic tools, equipment of assembly workshops, wall mounted reels, carts and compressors.

## MARKING

AIRSOFT Ø inn x Ø out / Ø inn x th. 16 BAR [Batch number]

## Highly flexible hose for compressed air.

Five layers, in extra-flexible PVC, with high strength polyester reinforcement.

### ADVANTAGES

AIRSOFT PERFORMANCE sets a new standard of flexibility for compressed-air use. Its innovative and exclusive structure, the result of years of TRICOFLEX's know-how, offers an exceptional hose solution that combines extreme manageability with unyielding resistance. AIRSOFT PERFORMANCE works discreetly even in cold weather.

### CONNECTORS

Quick connectors, barbed or serrated grooved connectors. Band, worm drive, screw or butterfly clamps. Cap connectors. Swaged fittings can be used if they do not damage the hose.

### CHEMICAL RESISTANCE

See table pages 110 to 113 column B.



Ø mm	+/- mm	Ø mm	+/- mm	Ø mm	g/m	bar	bar	mm	Black	
									25 m	50 m
6,3	+/- 0,3	11	+/- 0,3	2,35	77	64	16	35	100050	100051
8	+/- 0,4	13	+/- 0,4	2,5	100	64	16	50	100052	100053
9	+/- 0,5	14,5	+/- 0,5	2,75	123	64	16	50	100054	100055
10	+/- 0,5	15,5	+/- 0,5	2,75	134	64	16	70	100056	100057
12,7	+/- 0,6	19	+/- 0,6	3,15	190	64	16	100	100058	100059
16	+/- 0,6	23	+/- 0,6	3,5	254	64	16	140	100060	100061
19	+/- 0,8	26,5	+/- 0,8	3,75	323	64	16	140	100062	100063
25	+/- 1,0	33,5	+/- 1,0	4,25	469	64	16	240	100064	100065



With presentation disc to Ø 12,7mm