




AIRSOFT PERFORMANCE




+60
-20
°C

64
 bar




- 1 Extra-soft smooth black non-staining and oil resistant PVC
- 2 4 Intermediate layer in extra-soft black PVC
- 3 Polyester reinforcement
- 5 Extra-soft red oil resistant PVC

APPLICATIONS

Pneumatic tools, equipment of assembly workshops, wall mounted reels, carts and compressors.



MARKING

AIRSOFT Ø inn x Ø out / Ø inn x th. 16 BAR  [Batch number]

Highly flexible hose for compressed air.

Five layers, in extra-flexible PVC, with high strength polyester reinforcement.

ADVANTAGES








AIRSOFT PERFORMANCE sets a new standard of flexibility for compressed-air use. Its innovative and exclusive structure, the result of years of TRICOFLEX's know-how, offers an exceptional hose solution that combines extreme manageability with unyielding resistance. AIRSOFT PERFORMANCE works discreetly even in cold weather.

CONNECTORS

Quick connectors, barbed or serrated grooved connectors. Band, worm drive, screw or butterfly clamps. Cap connectors. Swaged fittings can be used if they do not damage the hose.

CHEMICAL RESISTANCE

See table pages 110 to 113 column B.

 mm	+/- mm	 mm	+/- mm	 mm	 g/m	 bar	 bar	 mm	Black	
									25 m	50 m
6,3	+/-0.3	11	+/-0.3	2,35	77	64	16	35	100050	100051
8	+/-0.4	13	+/-0.4	2,5	100	64	16	50	100052	100053
9	+/-0.5	14,5	+/-0.5	2,75	123	64	16	50	100054	100055
10	+/-0.5	15,5	+/-0.5	2,75	134	64	16	70	100056	100057
12,7	+/-0.6	19	+/-0.6	3,15	190	64	16	100	100058	100059
16	+/-0.6	23	+/-0.6	3,5	254	64	16	140	100060	100061
19	+/-0.8	26,5	+/-0.8	3,75	323	64	16	140	100062	100063
25	+/-1.0	33,5	+/-1.0	4,25	469	64	16	240	100064	100065



With presentation disc to Ø 12,7mm