


SIMULANTS A, B, C

- fruit juices
- wines

(EU) N°10/2011

+60
- 15
°C

1 Food grade transparent PVC


APPLICATIONS

Carrying non fatty foodstuffs or light alcohols, non-pressurised aqueous liquids.



MARKING

(EU) N° 10/2011 Sim. A, B, C [Batch number]

Single layer PVC tube in flexible, transparent PVC.

CONNECTORS

Barbed or serrated connectors with band or butterfly clamps. Swaged fittings are unsuitable.

CHEMICAL RESISTANCE

See table pages 110 to 113 column A.
Not hydrocarbon resistant.

	+/-			+/-		Transparent		
						25 m	50 m	100 m
4	+/-0,2	6	1	+/-0,2	19			141040
4	+/-0,2	7	1,5	+/-0,2	31		069141	
5	+/-0,2	8	1,5	+/-0,2	37		069167	
6	+/-0,3	9	1,5	+/-0,2	43		069286	
7	+/-0,4	10	1,5	+/-0,2	49		069290	
8	+/-0,4	10	1	+/-0,2	34		069326	
8	+/-0,4	11	1,5	+/-0,2	54		069328	
8	+/-0,5	12	2	+/-0,2	75		141266	
9	+/-0,5	12	1,5	+/-0,2	60		093910	
10	+/-0,5	13	1,5	+/-0,2	66		069330	
10	+/-0,5	14	2	+/-0,2	90		141369	
10	+/-0,5	16	3	+/-0,3	147		141372	
12	+/-0,5	15	1,5	+/-0,3	77		069340	
12	+/-0,5	16	2	+/-0,3	106		069360	
15	+/-0,8	19	2	+/-0,3	130		141919	
16	+/-0,8	20	2	+/-0,3	138		141501	
16	+/-0,8	21	2,5	+/-0,3	176		141505	
19	+/-0,8	24	2,5	+/-0,3	205		141510	
20	+/-0,8	26	3	+/-0,3	260		141633	
25	+/-1,0	31	3	+/-0,3	317	141662		
30	+/-1,0	37	3,5	+/-0,4	442	141720		
38	+/-1,0	48	5	+/-0,5	818	141817		