




GAINE GA2



- 1 Spiral in rigid PVC
2 Wall in soft grey PVC

APPLICATIONS

Ventilation, suction of air and fumes, agricultural spraying.



MARKING

GA2 Ø inn [Batch number]

Flexible ducting in PVC for ventilation and fumes suction.

Reinforced with a rigid PVC spiral.

ADVANTAGES

Extremely lightweight and highly flexible, the GA2 ducting hose offers excellent mechanical resistance. Its smooth inner wall ensures minimal pressure loss.

CONNECTORS

Connectors with wire clamps or screwed fittings. (left hand spiral).

CHEMICAL RESISTANCE

See table pages 110 to 113 column A.

	+/- mm						Grey			
							10 m	20 m	30 m	50 m
20	±1.0	0,75	2,5	116	550	20				150708
25	±1.0	0,75	3	164	500	25				150711
35	±1.0	0,75	3	232	500	35				150737
38	±1.0	0,75	3	263	500	38				150795
40	±1.0	0,8	3,3	272	500	40				150740
50	±1.0	0,85	4	436	450	50			150753	
60	±1.0	0,85	4	524	400	60			035075	
70	±1.0	0,9	4	620	400	70			035088	
75	±1.0	0,9	4	670	400	75			150853	
80	±1.0	1	4	756	400	80			035133	
90	±1.0	1	4	806	400	90			035120	
100	±1.0	1	4	950	400	100		035098		
110	±1.1	1	4,5	1068	330	110		035104		
120	±1.2	1	4,5	1164	330	120		035146		
125	±1.3	1	5,5	1186	300	125		150811		
140	±1.4	1,1	4,5	1456	300	140		150766		
150	±1.5	1,1	5	1650	300	150		150779		
160	±1.6	1,1	5	1844	300	160	150782			
180	±1.8	1,1	5,5	2134	250	180	150824			
200	±2.0	1,1	5	2328	250	200	035117			
250	±2.5	1,1	6	3250	200	250	150837			