



GA3



1 Spiral in rigid shock-proof PVC
2 Wall in soft black PVC

APPLICATIONS

Ventilation, suction of air and fumes, small pumps and water delivery (3 bar max.), seed drills.



WITHOUT MARKING

Flexible ducting in PVC for ventilation and fumes suction.

Reinforced with a rigid PVC spiral.

ADVANTAGES

While being extremely lightweight and highly flexible, the GA3 ducting hose offers excellent mechanical resistance. It can also operate under pressure (maximum 3 bar). Its smooth inner wall ensures minimal pressure loss.

CONNECTORS

Connectors with wire clamps or screwed fittings (right hand spiral).

CHEMICAL RESISTANCE

See table pages 110 to 113 column A.

| | +/- mm | 1 mm | 2,5 mm | 105 g/m | 350 mbar | 30 mm | Black | |
|----|---------|------|--------|---------|----------|-------|--------|--------|
| | | | | | | | 25 m | 30 m |
| 12 | +/- 1,0 | 1 | 2,5 | 105 | 350 | 30 | | 167617 |
| 20 | +/- 1,0 | 1 | 2,5 | 160 | 350 | 35 | | 167620 |
| 25 | +/- 1,0 | 1 | 2,7 | 217 | 350 | 40 | | 167633 |
| 32 | +/- 1,0 | 1 | 3,1 | 260 | 350 | 45 | | 167646 |
| 40 | +/- 1,0 | 1 | 3,2 | 337 | 300 | 50 | 167659 | 167658 |