



SPIRABEL® BALNEO PISCINE

990
mbar21 | 15
bar+60
- 15
°C

- 1 White spiral in rigid PVC
- 2 Wall in soft and white PVC. Inner and outer smooth

APPLICATIONS

Swimmingpools and spas.

MARKING

SPIRABEL BALNEO Ø out  [Batch number]

Hose reinforced with a rigid spiral in a white soft PVC wall.

ADVANTAGES

The manufacturing process designed to make SPIRABEL® BALNEO assures smooth inner and outer walls and a high precision of the outer diameter. This brings a total compatibility with plastic connectors used for swimmingpools or spas.

This hose is highly resistant to crushing and vacuum.

CONNECTORS






Usual plastic connectors for swimming pool building.

CHEMICAL RESISTANCE

See table pages 110 to 113 column A.

WARNING

Spiral hoses in general have an elongation under pressure that can be important when temperature is above 40°C. This has to be considered before installation. We remain at your disposal for any question on this issue.

 mm	+/- mm	 g/m	 bar	 bar	 mm	White	
						25 m	50 m
32	+/-0.4	346	21	7	80	168729	
50	+/-0.4	675	18	6	190	168774	168780
63	+/-0.4	943	15	5	250	168793	

WARNING
designated by the
outside diameter