




# SPIRABEL® GMDS



**950**  
mbar

**15 | 9**  
bar

**+60**  
**- 15**  
°C



- 1 Shock-proof spiral reinforcement  
2 Flexible PVC green wall

## APPLICATIONS

Multipurpose.

## MARKING

SPIRABEL GMDS Ø inn [Batch number]

## Multipurpose hose.

Reinforced with a white, rigid and shock-proof PVC spiral in a soft PVC wall.

## ADVANTAGES

SPIRABEL® GMDS is a resistant, flexible and economic hose. Its very smooth internal wall reduces the flow losses.

## CONNECTORS

Guillemín or Storz symmetrical connectors, cam or universal joint connectors – Fastened with single-thread or spiral clamps (SERFLEX). Crimping and band clamps are not recommended as they do not ensure a perfect leak proof connection and increase the risk of the spiral being crushed and breaking.

## CHEMICAL RESISTANCE

See table pages 110 to 113 column A.  
We recommend to use SPIRABEL® MDSO or SPIRABEL® PUA2 for the transfer of hydrocarbons.

## WARNING

Spiral hoses in general have an elongation under pressure that can be important when temperature is above 40°C. This has to be considered before installation. We remain at your disposal for any question on this issue.

mm	+/- mm	mm	g/m	bar	bar	mbar	m	Green 30 m
25	+/-0.8	3,4	360	15	5	950	60	033207
32	+/-0.8	3,5	460	15	5	950	75	034380
38	+/-0.8	3,7	570	15	5	950	90	034383
51	+/-1.0	4,3	830	15	5	950	95	033233
63	+/-1.0	4,4	1050	12	4	950	115	034193
76	+/-1.0	5,3	1470	12	4	950	120	033255
102	+/-1.0	6,3	2165	9	3	950	180	033920
152	+/-1.0	7,2	4220	9	3	950	320	148914