




SPIRABEL® LD*



	600	18 9	+60
mbar	bar	-15	°C



1 White spiral in rigid and shock-proof PVC
2 Wall in soft and transparent PVC. Inner and outer smooth

APPLICATIONS

Suction and delivery light duty, watering, small pumps, seed drills.



MARKING

SPIRABEL LD Ø inn [Batch number]

Flexible hose reinforced with a white shock-proof PVC spiral. Soft and transparent PVC wall. Light duty.

ADVANTAGES

SPIRABEL® LD is a very light, flexible and economic hose. Its inner wall is smooth to reduce flow losses. Its transparency allows observation of transferred products.

CONNECTORS

Symmetrical connectors (Guillemin or Storz) with band clamps thanks to the smooth cover. We recommend checking before assembly that the fittings cannot harm the inner wall.

CHEMICAL RESISTANCE

See table pages 110 to 113 column A.

WARNING

Spiral hoses in general have an elongation under pressure that can be important when temperature is above 40°C. This has to be considered before installation. We remain at your disposal for any question on this issue.

Ø mm	+/- mm	Ø mm	g/m	bar	bar	mbar	mm	Transparent green wall		
								25 m	30 m	50 m
20	+/- 1,0	2,4	220	18	6	600	80			137315
25	+/- 1,0	2,4	270	15	5	600	105			137331
32	+/- 1,0	2,5	350	15	5	600	135			137357
38	+/- 0,6	2,8	460	15	5	600	160		137371	137373
40	+/- 0,6	2,9	500	15	5	600	180	134376		
50	+/- 0,6	3,3	710	12	4	600	230		137413	137415
63	+/- 1,0	3,5	870	12	4	600	265			134405
75	+/- 1,0	3,8	1000	12	4	600	315	134421		
102	+/- 1,0	4,2	1870	9	3	600	428	134489		



End-of-line product – available while stocks last. This item has now been replaced by SPIRABEL® SI - page 74.

You'll find the full cross-reference table on the inside back flap of the catalogue to help you choose the right product code.