




SUPER NOBELAIR®



- 1 Flexible beige PVC
- 2 Polyester reinforcement
- 3 Flexible black PVC

APPLICATIONS

Pneumatic tools, equipment of assembly workshops, wall mounted reels, carts and compressors.

MARKING

SUPER NOBELAIR  20 BAR [Batch number]

Hose for compressed air supply.

Three-layer design, in extra flexible PVC, with high resistant polyester fibre reinforcement.

ADVANTAGES

The balanced reinforcement of SUPER NOBELAIR® enables it to withstand high pressure with minimal distortion. Thus, it can withstand extended and frequent pressure impulse cycles.

The composition of this flexible and light hose provides it with good resistance to impacts and distortion.














Moreover, the PVC composition eliminates any risks of cracks appearing (particular defect of rubbers), thus improving safety and a long service life.

CONNECTORS

Quick connectors, barbed or serrated connectors. Band, worm drive, screw or butterfly clamps. Swaged fittings can be used if they do not damage the hose.

CHEMICAL RESISTANCE

See table pages 110 to 113 column A.

	+/- mm		+/- mm		g/m		bar		mm	Beige		
										25 m	50 m	100 m
6,3	+/- 0,3	11	+/- 0,3	2,35	85		60	20	45		198022	
7	+/- 0,4	12	+/- 0,4	2,5	90		60	20	49	198051		
8	+/- 0,4	13	+/- 0,4	2,5	107		60	20	56	198093	198106	198119
10	+/- 0,5	15,5	+/- 0,5	2,75	143		60	20	70	198177	198180	
12,7	+/- 0,6	19	+/- 0,6	3,15	205		60	20	89	198212	198225	198238
16	+/- 0,6	23	+/- 0,6	3,5	284		60	20	112	198254	198267	
19	+/- 0,8	26,5	+/- 0,8	3,75	352		60	20	145	198296	198309	198312
25	+/- 1,0	33,5	+/- 1,0	4,25	515		60	20	210	198338	198341	