



SUPER NOBELAIR® SOFT



- 1 Extra-flexible blue PVC
- 2 Polyester reinforcement
- 3 Extra-flexible black PVC

APPLICATIONS

Pneumatic tools, equipment of assembly workshops, wall mounted reels, carts and compressors.

MARKING

SUPER NOBELAIR SOFT Ø inn x Ø out / Ø inn x th. 15 BAR [Batch number]



Highly flexible hose for compressed air.

Three-layer design, in extra-flexible PVC, with high strength polyester reinforcement.

ADVANTAGES

Compounds specially developed for SUPER NOBELAIR® SOFT give it a high flexibility even at low temperature. This property, associated with lightness, makes the use of this hose easier; therefore the hose is particularly appreciated by users of pneumatic tools both outdoors and indoors. PVC structure eliminates any risk of cracks (flaws of a lot of rubber hoses), making this hose long lasting.

Thanks to a well balanced reinforcement, SUPER NOBELAIR® SOFT has a high pressure resistance with little distortion under pressure. So it can withstand long and frequent impulse cycles.

CONNECTORS

Quick connectors, barbed or serrated grooved connectors. Band, worm drive, screw or butterfly clamps. Cap connectors. Swaged fittings can be used if they do not damage the hose.

CHEMICAL RESISTANCE

See table pages 110 to 113 column A.

	+/- mm		+/- mm		mm		g/m		bar		bar		mm	Blue	
														25 m	50 m
6,3	+/-0,3	11	+/-0,3	2,35	81	60	15	45						148362	147753
8	+/-0,4	13	+/-0,4	2,5	106	60	15	56						148375	147766
9	+/-0,5	14,5	+/-0,5	2,75	131	60	15	63						148388	147772
10	+/-0,5	15,5	+/-0,5	2,75	141	60	15	70						148391	147785
12,7	+/-0,6	19	+/-0,6	3,15	200	60	15	89						147956	148162
16	+/-0,6	23	+/-0,6	3,5	265	60	15	112						158059	158062
19	+/-0,8	26,5	+/-0,8	3,75	337	60	15	145						158075	158088
25	+/-1,0	33,5	+/-1,0	4,25	493	60	15	210						158091	158104