



T 694

NF 021
02/01

www.marque-nf.com

T 694 HOSE COMPLIES WITH
NF EN 694:2014 STANDARD
(TYPE A CLASS 2)42 | 25
bar

+60

- 20



°C



- 1 Cover in black or red soft PVC
- 2 Polyester reinforcement
- 3 Inner layer in black soft PVC

MARKING

NF - EN 694:2014 - A - 2 - Ø inn - [WP] - [Quarter]Q/[Year] - NF - 02 - [Batch number]

Hose for fire-fighting reels - Black matt or red colour.

Three-layer hose according to NF EN 694:2014 (type A class 2), with polyester reinforcement.

ADVANTAGES








Its conception in very resistant materials allows T694 to easily withstand shocks and crushing.

It coils well without flattening on standard hose reels.

Thanks to the UV and abrasion resistant cover, T694 has excellent anti-aging properties.

CONNECTORS

Usual connections for fire-fighting hoses.

 mm	\pm mm	 mm	\pm mm	 mm	 g/m	 bar	 bar	 mm	Black	Red
	mm		mm						30 m	30 m
19	+/-0,6	25	+/-0,6	3	285	42	12	220	145336	145430
25	+/-0,8	32	+/-0,8	3,5	433	42	12	240	145378	145352
33	+/-1,0	41,5	+/-1,0	4,25	714	25	7	280	144672	