

TRICOFLEX® PERFORMANCE

















Intermediate layer of flexible PVC yellow

Textile knitted reinforcement TNT

Intermediate layer of soft black PVC

Red flexible PVC

FIVE-LAYER KNIT WATER TRANSPORT HOSE FOR PROFESSIONAL USE.

APPLICATIONS

Watering, irrigation, water supply and delivery

SECTORS OF ACTIVITY

Farms, vegetable growers, horticulture, water supply and delivery in industry, construction sites and road

MARKING

TRICOFLEX PERFORMANCE Tricoflex Non Torsion Technology ~ [N° lot]

See table pages 114 to 117 column A.

CHEMICAL RESISTANCE

ADVANTAGES

TRICOFLEX® PERFORMANCE combines high resistance and exceptional flexibility thanks to a Multilayered structure and an exclusive knit technique.

Resistant to abrasion, bad weather conditions, UV, crushing, and repeated pressure cycles, with a low curve radius preventing folding: these intrinsic qualities make the difference every day and for the long term.

TRICOFLEX® PERFORMANCE even has a red interior wall specially formulated to improve flow and resisted to polluted water, for a longer life span even in the case of especially tough use.

CONNECTORS

Connectors with band, screw or 'O' type clamps. Automatic connectors for watering.



			4.0				
	\cap				Yellow		OW
			bar	bar	mm	25 m	50 m
12,5	18,2	2,85	38	15	110	110000	110001
15	20,8	2,9	35	14	120	110002	110003
19	25,8	3,4	30	12	160	110004	110005
25	32,4	3,7	20	8	200	110006	110007