



TRICOFLEX® PERFORMANCE



38 | 20
bar

+60
- 20
°C



- 1 Soft PVC coating
- 2 Intermediate layer of flexible PVC yellow
- 3 Textile knitted reinforcement TNT
- 4 Intermediate layer of soft black PVC
- 5 Red flexible PVC

APPLICATIONS

Watering, irrigation, water supply and delivery.

MARKING

TRICOFLEX PERFORMANCE Tricoflex Non Torsion Technology  [N° lot]

Five-layer knit water transport hose for professional use.

ADVANTAGES

TRICOFLEX® PERFORMANCE offers both high resistance and exceptional flexibility, thanks to its multilayered design and exclusive knit technology.

Built to withstand abrasion, harsh weather, UV exposure, crushing, and repeated pressure cycles, its low curve radius prevents folding, ensuring long-lasting performance day after day. For even greater durability, TRICOFLEX® PERFORMANCE features a specially formulated red inner wall that enhances flow and resists polluted water, making it ideal for demanding conditions and extended use..







CONNECTORS

Connectors with band, screw or 'O' type clamps.
Automatic connectors for watering.

CHEMICAL RESISTANCE

See table pages 110 to 113 column A.



						Yellow	
						25 m	50 m
12,5	18,2	2,85	38	15	110	110000	110001
15	20,8	2,9	35	14	120	110002	110003
19	25,8	3,4	30	12	160	110004	110005
25	32,4	3,7	20	8	200	110006	110007