



WINDFLEX® 600 PU AL



SIMULANTS A, B, C, D1

- fruit juices
- wines
- alcohols
- milk

250 | 10
mbar

+90

-40



°C



- 1 Copper color steel spiral
- 2 Wall in transparent polyurethane



APPLICATIONS

Suction of: Sawdust and chips, air and fumes, oil vapour extraction.



MARKING

↓ WINDFLEX® 600 PU (EU) N°10/2011 ↓ Ø inn

[Batch number]
Made in France

Flexible ducting in polyurethane ether with wall reinforced with a galvanized steel wire helix. Spring Quality.

Potential equalisation, earthed at the ends of the steel spiral. PU rated non flammable UL94 V2. Halogen free.

	+/-					Transparent	
						5 m	10 m
40	0/+2,0	0,6	250	250	25		174720
51	0/+2,0	0,6	290	250	32		174721
60	0/+2,0	0,6	340	200	37		174719*
70	0/+3,0	0,6	430	140	43		174731
80	0/+3,0	0,6	500	100	49		174760*
90	0/+3,0	0,6	550	100	56		174761*
102	0/+4,0	0,6	560	90	63		174722
120	0/+4,0	0,6	710	80	74		174723
127	0/+4,0	0,6	750	80	78		174730
140	0/+4,0	0,6	830	80	86		174762*
152	0/+5,0	0,6	900	60	94		174724
160	0/+5,0	0,6	940	60	99		174725
180	0/+5,0	0,6	1060	50	111		174726
203	0/+5,0	0,6	1250	50	125		174727
254	0/+5,0	0,6	1560	50	157		174728
305	0/+6,0	0,6	1880	30	188		174729
350	0/+6,0	0,6	2620	20	216		174763*
400	0/+6,0	0,6	3000	20	247	174764*	
500	0/+6,0	0,6	3750	10	309	174765*	
600	0/+6,0	0,6	5000	10	370	174614*	



ADVANTAGES

WINDFLEX® 600 PU AL ducting is extremely flexible and due to the 100% ether-based polyurethane wall offers very good mechanical resistance. Extremely good abrasion resistance, flexibility and elasticity. Remarkable for its wide temperature range of use.

CONNECTORS

Connectors with wire clamps. Small diameters can be screwed into themselves. We recommend checking before assembly that the fittings cannot harm the inner wall.

CHEMICAL RESISTANCE

See table pages 110 to 113 column C.

delivery in coils
except compressed articles

WE HAVE THE POSSIBILITY
TO MANUFACTURE OTHER LENGTHS
AND DIAMETERS ON REQUEST.
CONSULT US.