

AIR-JET



- 1 Abrasion resistant TPU coating.
- 2 Intermediate, extra-flexible crystal TPU layer
- 3 Textile reinforcement
- 4 Black antistatic TPU inner wall

ANTISTATIC HOSE SPECIALLY DESIGNED FOR COMPRESSED AIR SUPPLIES.

Design using four layers of extra-flexible TPU with a high tenacity polyester fibre reinforcement.

APPLICATIONS

Hose specially designed for compressed air supplies in arduous and/or high risk environments: compressed air stations for pneumatic tools, compressors, paint sprayers with tanks

SECTORS OF ACTIVITY

Garages, automotive industry, plastics industry, assembly plants.

Resistivity $< 10^6 \Omega/m$
complies with NF EN ISO 8031

MARKING

= AIR JET - TUYAU AIR DISSIPATEUR _DISSIPATER AIR HOSE - Ø INT _Ø Connectors ID - PMS/MWP
20BAR/290PSI @ 20°C/68°F - «Year of manufacturing» - MADE IN FRANCE = [Batch number]

ADVANTAGES








AIR-JET's design gives it exceptional flexibility and strength. Its very light weight makes it easy to handle. Its balanced reinforcement allows it to withstand pressure with only minimal deformation. It can therefore withstand long and frequent pressure pulses, guaranteeing a long service life and safety. The inner and outer PE sheaths make it compatible with cleaning using solvents.

CONNECTORS

To protect electric continuity, provide for metal fittings: NPS, express, hose or grooved quick couplings, metal clamps or ear clamps. Quick fittings Crimping is possible with non-damaging fittings. Before assembly, make sure the tip does not damage the inner pipe (especially the case of improperly deburred and therefore cutting fittings).

CHEMICAL RESISTANCE

See the chemical resistance table column C.

 mm	+/- mm	 mm	+/- mm	 mm	 g/m	 bar	 bar	 mm	Turquoise					
									25 m	152,5 m	175 m	200 m	250 m	
6,5	+/-0,5	10,5	+/-0,5	2	61	60	20	60						125274
8	+/-0,5	12	+/-0,5	2	72	60	20	70	125285	125286		125287		
9,5	+/-0,5	14	+/-0,6	2,25	100	60	20	80		125489	125490			



FLEXI SPRAY'S ASSEMBLIES



Fittings 1/4"			
⊗ (mm)	L (m)	Ref	Mini ord (PC/cart)
3,2	7,5	126021	15
	10	126022	10
6,5	5	126121	8
	7,5	126122	8
	10	126123	7

Fittings 3/8"			
⊗ (mm)	L (m)	Ref	Mini ord (PC/cart)
3,2	7,5	126023	15
	10	126024	10
6,5	5	126124	8
	7,5	126125	8
	10	126126	7
9,5	5	126155	8
	7,5	126156	8
	10	126157	6

AIR JET'S ASSEMBLIES



Fittings 1/4"			
⊗ (mm)	L (m)	Ref	Mini ord (PC/cart)
6,5	5	125275	8
	7,5	125276	8
	10	125277	7
	15	125278	4
8	7,5	125288	8
	10	125289	6
	15	125290	6
9,5	5	125491	8
	7,5	125492	8
	15	125493	4