





WINDFLEX® 805 EH



1 Sheathed steel spiral
2 Wall in transparent polyurethane



APPLICATIONS

Suction and transfer of all types of powders, pellets, filings, and shavings.

MARKING

↓ WINDFLEX® 805 PU EH ↓ Ø inn

[Batch number]
Made in France

Flexible ether-based polyurethane ducting, reinforced by a spring-loaded quality copper-plated steel coil embedded in the wall.

Electrical bonding by earthing the steel coil. UL94 V2 certified non-flammable polyurethane.

	mm	+/- mm	mm	g/m	mbar	mm	Transparent
180	0/+5,0	0,7	1950	120	200	174824*	10 m
200	0/+5,0	0,8	2200	100	222	174825*	

ADVANTAGES

The WINDFLEX® 805 EH ducting offers an excellent compromise between impressive flexibility and tested mechanical resistance. Its wall thickness and helical pitch are adapted to different diameters in order to respond to the needs of today.

CONNECTORS

Regular single-wire sleeve clamps. Simply screwing two lengths of the same diameter together may also be possible in some cases (with small diameters). Before assembly, make sure that the connector is not hazardous to the inner tube (particularly in the case of poorly fettled and therefore sharp fittings).

CHEMICAL RESISTANCE

See the Chemical resistance Chart of Hoses pages 110 to 113 column C.

Delivery in coils

WE HAVE THE POSSIBILITY
TO MANUFACTURE OTHER LENGTHS
AND DIAMETERS ON REQUEST.
CONSULT US.